

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	<b>SMK 5170 SEMKYD CFA 31 X 70 PU</b>	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	<b>1/ 11</b>

## 1. SUBSTANCE/ MIXTURE AND COMPANY/ EMPLOYER IDENTIFICATION

### 1.1 Substance/ Mixture Identification:

Product Name: **SEMKYD CFA 31 X 70 PU– SMK 5170**

### 1.2 Use of Material / Composition and If not recommended Use:

It is used in paint and varnish production.

### 1.3 Company Identification

#### Producer Company

Name: SEMKİM Paint and Chemicals Industry and Trade Ltd. Co.

Address: Kemalpaşa OSB Mah. 508 Sokak No 320 Kemalpaşa/İZMİR

Phone Number: 0232 878 97 80

Fax: 0232 878 97 83

E-posta: info@semkim.com

### 1.4 In case of emergency: 114 (UZEM)

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of Substance/Mixture

<b>Physical Effect</b>	Flammable Liquid Category 3	H226
<b>Health Effect</b>	Skin Irritation 2	H315
<b>Environmental Effect</b>	No application	

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	<b>SMK 5170</b> <b>SEMKYD CFA 31 X 70 PU</b>	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	<b>2/ 11</b>

## 2.2 Label Elements



**GHS Symbol:**

**Signal Word:** Warning

### **Hazard Statements**

H226: Flammable liquid and vapor.

H315: Causes skin irritation.

### **Precautionary Statements**

P210: Keep away from heat/sparks/flame/hot surfaces.- No smoking.

P233: Keep the container tightly closed.

P240: Do sit in the ground receiving equipment and container.

P241: Use explosion-proof electrical / ventilation / ignition material.

P242: Only use fireproof tool.

P243: Take precautionary measures against static discharge.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protector.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse SKIN with water/shower.

P332+P313: IF SKIN irritation is present: Get medical attention / intervention.

P362: Remove your contaminated clothing and wash it before using it again.

P370+P378: In case of fire use CO<sub>2</sub>, foam or dry powder for extinguishing.

P403+P235: Store in a well-ventilated area. Keep cold.

P501: Please dispose of contents/container.

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK 5170 SEMKYD CFA 31 X 70 PU	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	3/ 11

### 3. INFORMATION ON COMPOSITION CONTENT

Substance Name	CAS No	EC No	REACH No	Content %	Hazard Code and Category Code	Hazard Statement Code
Xylene	95-47-6	202-422-2	01- 2119485822- 30-0023	30	Flammable Liq. 3 Acute Tox. 4 Acute. Tox. 4 Skin Irritation 2	H226 H332 H312 H315
Alkyd Resin				70		

### 4. FIRST AID MEASURES

#### 4.1 Description of first-aid measures

**Inhalation:** Get medical help immediately. Move away from the environment and immediately into fresh air. If not breathing, do artificial respiration. If breathing difficulties give oxygen.

**Skin Contact:** Get medical help immediately. Remove contaminated clothing and shoes and immediately wash your skin with plenty of water for at least 15 minutes.

**Eye Contact:** Wash immediately with large quantities of water for 15 minutes. If irritation persist call a doctor.

**Ingestion:** Do not induce vomiting. Chemical vapors may escape during lungs. Immediately give 1-2 cups of water or milk to the person. If consciousness is off, never give anything. Get medical help urgently.

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	<b>SMK 5170 SEMKYD CFA 31 X 70 PU</b>	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	<b>4/ 11</b>

#### **4.2 Most important symptoms and effects, both acute and delayed**

The known symptoms and effects are indicated on the label. (See Section 2.2)

#### **4.3 Indication of immediate medical attention and special treatment needed, if necessary**

Support psychologically and behave according to findings.

### **5. FIREFIGHTING MEASURES**

#### **5.1 Extinguishing media**

To put out the fire foam, dry chemical powder and use the CO<sub>2</sub> extinguishing devices. **DO NOT STRICTLY INTERFERE WITH WATER.**

#### **5.2 Specific damage caused by substance and mixture**

Serious fire hazard.

#### **5.3 Advice for firefighters**

If there is no risk, move the container away from the fire area. Cool containers with water spray until the flames completely extinguish.

### **6. ACCIDENTAL RELEASE MEASURES**

#### **6.1 Personal protective precautions**

Avoid breathing vapor, fume or gas. Make sure that the ventilation is sufficient. Destroy everything that could cause ignition. Remove the personnel safe zone. Wear suitable protective clothing.

#### **6.2 Environmental precautions**

Be careful not to leak or spill. Avoid sewage, water spills, and spills on the soil.

#### **6.3 Methods and material for containment and cleaning up**

In case of small spills, clean with sand, earth or cloth. Collect the materials used for cleaning in a separate place and dispose of them according to the hazardous waste regulations. No smoking in the place where the waste is collected, no welding, no naked fire. Ventilate the environment well.

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	<b>SMK 5170 SEMKYD CFA 31 X 70 PU</b>	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	<b>5/ 11</b>

If it spreads in large quantities, turn off all heat and sources of ignition, do not smoke. The person who cleans this area should wear a sword.

## 7. STORAGE AND HANDLING

### 7.1 Precautions for safe handling

#### 7.1.1

Measures to prevent or control both fire and aerosol and dust formation to ensure safe handling of the substance or mixture.

Prevention of the handling of substances or mixtures which are incompatible with each other.

Reduce the spread of the substance or mixture to the environment, such as avoiding spillage or keeping it away from waterways.

#### 7.1.2

No eating, drinking and smoking in work areas.

Washing hands after use.

Removal of contaminated clothing and protective equipment before entering food areas.

### 7.2 Conditions for safe stage, including any incompatibilities

**Hazards and Precautions** Flammable liquid and vapor. The mouth of the resin containers must be sealed very tightly. Even the smallest amount of material remaining in empty containers can be dangerous. Be sure not to weld the containers, be careful of static electricity, before making sure that they are emptied. The containers must be filled with water and should not be repaired without ensuring that all resin vapors have been thrown out.

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	<b>SMK 5170 SEMKYD CFA 31 X 70 PU</b>	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	<b>6/ 11</b>

**Transport:** The resin is transported while the mouths of the containers are tightly closed. Keep away from all sources of heat and flame. All vehicles must be grounded.

**Storage :** Storage area away from fire, sparks and it must be a cool place with air flow.

### 7.3 Specific end use

No data.

## 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

### 8.1 Control Parameters

#### Exposure Limits/ standards

The places where this material is used and stored should have adequate ventilation.

### 8.2 Exposure Controls

**8.2.1 Engineering Precautions:** Carry it according to industrial hygiene and safety regulations. Wash your hands at the end of the day.

#### 8.2.2 Personal Protective Equipment



**Inhalation Protection:** Use respiratory equipment and devices that have been tested and approved in accordance with the standard.

**Eye/Face Protection:** Use protective glasses or face shields against chemical spatter that tightly enclose the face.

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK 5170 SEMKYD CFA 31 X 70 PU	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	7/ 11

**Skin Protection:** Use suitable gloves. Gloves should be checked before use. Contaminated gloves should be disposed of in accordance with good laboratory practices and compliance rules. Away from synthetic clothing that can produce static electricity. This information is advisory. It should not be accepted as an approval for any particular use case.

**Hands Protection:** If skin contact is indicated, use a chemically resistant, waterproof glove complying with an approved standard.

**Thermal Damage:** All protective equipment suitable for use at high temperatures should be used.

### 8.3 Environmental Exposure Control

Ventilation emissions and work process equipment must be checked for compliance with environmental protection legislation requirements.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on Basic Physical and Chemical Properties

<b>Form</b>	Consistent Liquid
<b>Odour</b>	The smell of the solvent
<b>Colour Gardner</b>	MAX 3
<b>Boiling Point</b>	144 °C (Xylene)
<b>Flash Point</b>	32 °C (Xylene)
<b>Evaporation Rate</b>	No data.
<b>Flammability</b>	Flammable
<b>Upper / lower flammability or explosive limits:</b>	0.9 %v- 6.7%v (Xylene)
<b>Vapor Pressure (25°C)</b>	882 kPa (Xylene)
<b>Vapor Density</b>	No data
<b>Solubility in water</b>	Insoluble.

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	<b>SMK 5170 SEMKYD CFA 31 X 70 PU</b>	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	<b>8/ 11</b>

<b>Viscosity ( DIN6/25 °C)</b>	350-400 seconds
<b>Viscosity (25 °C) Pa.s</b>	8-11
<b>Acid Number</b>	MAX 10
<b>Solid</b>	%70 ± 2
<b>Density (g/cm<sup>3</sup>)</b>	1,06±0,02

## 9.2 Other Information

No data.

## 10. STABILITY AND REACTIVITY

### 10.1 The Reaction

It is stable under normal conditions.

### 10.2 Chemical Stability

No dangerous polymerization occurs..

### 10.3 Harmful Response Potential

No data.

### 10.4 Conditions to Avoid

Heat, flame, sustainable sources.

### 10.5 Substances to Avoid

None

### 10.6 Hazardous Decomposition Products

No known hazardous decomposition products.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information of toxic effect

#### Acute Toxicity

Product/ ingredient	Test	Dose
Xylenes	LD50, Oral	3,523 mg/kg bw (rat)



# SAFETY DATA SHEET

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	<b>SMK 5170</b> <b>SEMKYD CFA 31 X 70 PU</b>	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	<b>9/ 11</b>

	LC50, Inhalation	27,124 mg/m <sup>3</sup> (rat vapors,4h)
	LD50, Dermal	12,126 mg/ kg ( rabbit)

**Skin Irritation or Corrosion:** Causes skin irritation

**Eye Irritation:** Causes serious eye irritation

**Skin Sensitization:** Not classified as a sensitizer

**Mutagenicity:** Genetic toxicity: Negative

**Carcinogenicity:**

Not classification of mixed xylenes streams for carcinogenicity is warranted under DPD or GHS/CLP.

**Reproductive Toxicity:**

Mixed xylenes, xylene isomers and ethylbenzene do not warrant classification for reproductive or developmental toxicity according to DPD or CLP.

**Inhalation-Repeated Dose Toxicity:**

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**Chronic/Other Effects:**

There are no specific data on neurotoxicity in humans by monoexposure to ethylbenzene or xylenes, but for aromatic solvents such as there is evidence for such effects in humans and animals.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

It does not accumulate in water organisms.

### 12.2 Persistence and Degradability

No data.

### 12.3 Bioaccumulation and Potential

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	<b>SMK 5170 SEMKYD CFA 31 X 70 PU</b>	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	<b>10/ 11</b>

No data.

#### **12.4 Mobility in Soil**

Stop it from getting in the ground.

#### **12.5 Results of PBT and vPvB Assessment**

No data.

#### **12.6 Other Information**

No data.

### **13. DISPOSAL CONSIDERATIONS**

#### **13.1 Waste Processing Methods**

It is disposed in accordance with the environmental regulations. Resin-carrying containers are cleaned and reused in accordance with regulations. Disposal of containers with resin is carried out at licensed disposal facilities.

### **14. TRANSPORT INFORMATION**

**14.1 UN No:** 1263

**14.2 Proper UN Transport Name:** UN 1263 PAINT RELATED MATERIAL

**14.3 Hazard Class:** 3

**14.4 Packing Group:** III

**14.5 Environmental Hazard:** There is no environmental damage.

**14.6 Special Precautions for the User:** No data.

### **15. REGULATORY INFORMATION**

#### **15.1 Special safety, health and environmental legislation for substance or mixture**

Regulation on the Classification, Labeling and Packing of Substance and Mixtures [R.G. 11/12/2013 - 28848]

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	<b>SMK 5170 SEMKYD CFA 31 X 70 PU</b>	Preparation date	05.05.2016
		Repreparation date	10.05.2020
Form No	12	Revision	3
		Page No	<b>11/ 11</b>

Regulation on Safety Data Sheets for Hazardous Substances and Mixtures [13/12/2014 - Official Gazette No. 29204]

Regulation on the Transport of Dangerous Goods by Road [R.G. 24/10/2013 - 28801]

## 16. OTHER INFORMATION

Update: The new format is applied.

Abbreviations: UZEM: National Poison Advisory Center

Key Information Sources: This GBF SEA regulation is based on the information in Appendix 6.

Hazard Statements: H 312: Harmful in contact with skin.

H 332: Harmful if inhaled.

Prepared by

Name Surname: PENBEGÜL İNCE

Contact: penbegul.ince@semkim.com.tr

Certification No: TÜV/01.154.08

Certification Effective Date: 09/05/2021