SEMKIM PAINT AND CHEMICALS INDUSTRY AND TRADE LIMITED COMPANY

Document : SEMSD-02/04 First published : 24.01.2012 Revision Date : 15.03.2017

Page : 1/1

## "MAGIC IN PAINTS"

# **SMK-0360 SEMKYD CFA 36 BG 60**

#### **DESCRIPTION**

**SMK-0360** is a Coconut Oil Fatty Acid Based Stoving/Reactive/NC Combination Short Oil Alkyd Resin

## **PRINCIPLE PROPERTIES**

- ✓ Very light coloured transparent film
- √ Vey good chemical and mechanical resistance
- ✓ Very high yellowing resistance
- ✓ Very high gloss and gloss retention

## **RECOMENDED APPLICATIONS**

- ✓ In combination with Amino Resins for high reactive primers and Top Coats
- ✓ Hammertone paints
- ✓ Laquers for Can Top Coating

### **SOLUBILITY**

Solvent Type	Solubility	
Toluene	+	
Xylene	+	
White Spirit	-	
n-Buthanol	-	
Methy-Ethyl Ketones	+	
Glycol Ethers	+	

#### **COMPATIBILITY**

Resin Type	Compatibility	
Rosin Esters	-	
Amino Resins	+	
Short Oil Alkyds	+	
Medium Oil Alkyds	-	
Long Oil Alkyds	-	
Aliphatic Hardeners	+	
Aromatic Hardeners	+	
Cellulosic Resin	+	

Kemalpasa OSB Mh. 508 Sk. No:320, P:35730, Kemalpasa, İZMİR - TURKEY

#### **TECHNICAL SPECIFICATIONS**

Composition			
Oil type	Coconut Oil Fatty acid		
Oil Lenght, %	~36 %		
Solvent	Butyl Glycol & Sol.100		
PA Content, %	~39 %		
%OH	~ 4		
Test	Range	Method	
Non Volatile, %	60±2 %	ISO 3251	
Viscosity (25°C) Pa.s	1 - 3	ISO 3219	
Acid Value (mgKOH/g)	10 max	ISO 2114	
Color (Gardner)	5 max	ISO 4630-2	
Density (g/cm³)	1.02±0,02	ISO 2811-1	

#### **PACKAGING AND DELIVERY FORM**

Resin is supplied in steel drum with net content of 200 Kg per drum. For the other package condition, please contact with us.

## **RECOMMENDED CURING COMBINATIONS**

Calculated Usage Rates

SMK 0360/Amino resins 2/1-3/1-3/2-4/1 SMK 0360/Cellülosic Resin 1/1-3/2-2/1

Oven Aplications Conditions 10' at 160 °C or 30' at 130 °C

#### **STORAGE AND SHELF LIFE**

Store in at temperatures between 5-30 °C, well-sealed packaging, dry and well-ventilated storage, should be avoided from direct sunlight.

Storage Shelf Life - 12 months from date of production.

#### **MATERIAL SAFETY**

Before handling the product , SDS of **SMK-0360** should always be read and well understood. Safety prodecures should be followed.

SEMFR-13

This document is prepared by SEMKIM authorized person. To more information please visit www.semkim.com.tr

Tel: +90 232 878 97 80 (Pbx) Fax: +90 232 878 97 83

info@semkim.com.tr