

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ witxture Ivalle	SEMKYD FA 50 W 60	Repreparation date	-
Form No	41	Revision	-
		Page No	1/ 12

### 1. SUBSTANCE/ MIXTURE AND COMPANY/ EMPLOYER IDENTIFICATION

#### **1.1 Substance/ Mixture Identification:**

Product Name: SEMKYD FA 50 W 60/ SMK-6001

#### 1.2 Use of Material / Composition and If not recommended Use:

Component of coating or paint

#### **1.3 Company Identification**

#### **Producer Company**

Name: SEMKİM Paint and Chemicals Industry and Trade Ltd. Co.

Address: Kemalpaşa OSB Mah. 508 Sokak No 320 Kemalpaşa/İZMİR

Phone Number: 0232 878 97 80

Fax: 0232 878 97 83

E-posta: info@semkim.com

#### **1.4 In case of emergency:** 114 (UZEM)

## 2. HAZARDS IDENTIFICATION

#### **2.1 Classification of Substance/Mixture**

Physical Effect	Flammable Liquid Category 3	H226
Health Effect	STOT (Single Exposure) Category 3	H336
incutin Enfect	STOT (Repeated Exposure) Category 2	H372
Environmental Effect	Aquatic Chronic 2	H411



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name SMK-6001		Preparation date	24.06.2020
	SEMKYD FA 50 W 60	Repreparation date	-
Form No 41	Revision	-	
	41	Page No	2/ 12

#### **2.2 Label Elements**



**GHS Symbol:** 

Signal Word: Danger

#### **Hazard Statements**

EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapor.

H336: May cause drowsiness or dizziness.

H372: Long term or repeated exposure may cause damage to organs.

H411: Toxic to aquatic life with long lasting effects.

#### **Precautionary Statements**

P210: Keep away from heat/sparks/flame/hot surfaces.- No smoking.

P233: Keep the container tightly closed.

P240: Do sit in the ground receiving equipment and container.

P241: Use explosion-proof electrical / ventilation / ignition/ material.

P242: Only use fireproof tool.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust / fume / gas / mist / vapor / spray.

P264: Wash thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well- ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protector.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ whitture ivalle	SEMKYD FA 50 W 60	Repreparation date	-
Form No	Form No 41	Revision	-
1 Olini 140		Page No	3/ 12

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P304+P340: IF INHALATION: Remove the fresh air and the damaged person easily breathe and hold in a comfortable position.

P312: If you do not feel well, call 114 NATIONAL POISON ADVISORY CENTER or call doctor / physician.

P314: If you do not feel well, we receive medical advice / intervention.

P370+P378: In case of fire use CO2, foam or dry powder for extinguishing.

P403+P233: Store in a well-ventilated area. Keep the container tightly closed.

P403+P235: Store in a well-ventilated area. Keep cold.

P405: Keep it under lock.

P501: Please dispose of contents/container.

## 3. INFORMATION ON COMPOSITION CONTENT

Substance	CAS No	EC No	Reach No	Content	Hazard Code and	Hazard
Name				%	Category Code	Statement Code
						H226
			01-		Flammable Liq. Cat.3	H304
Wilsite			-		Asp. Tox. Cat. 1	H372
White	64742-82-1	919-446-0	21194580	40	STOT (Repeated) Cat.1	H336
Spirit			49-33-		STOT (Single) Cat. 3	H411
			0007		Aquatic Chronic Cat. 2	EUH066
Alkyd				60		
Resin				60		



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
	SEMKYD FA 50 W 60	Repreparation date	-
Form No	41	Revision	-
		Page No	4/ 12

### 4. FIRST AID MEASURES

#### 4.1 Description of first-aid measures

**Inhalation:** Get medical help immediately. Move away from the environment and immediately into fresh air. If not breathing, do artificial respiration. If breathing difficulties give oxygen.

**Skin Contact:** Get medical help immediately. Remove contaminated clothing and shoes and immediately wash your skin with plenty of water for at least 15 minutes.

**Eye Contact**: Wash immediately with large quantities of water for 15 minutes. If irritation persist call a doctor.

**Ingestion:** Do not induce vomiting. Chemical vapors may escape during lungs. Immediately give 1-2 cups of water or milk to the person. If consciousness is off, never give anything. Get medical help urgently.

#### 4.2 Most important symptoms and effects, both acute and delayed

The known symptoms and effects are indicated on the label. (See Section 2.2)

**4.3 Indication of immediate medical attention and special treatment needed, if necessary** Support psychologically and behave according to findings.

### 5. FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

To put out the fire foam, dry chemical powder and use the CO<sub>2</sub> extinguishing devices. **DO NOT STRICTLY INTERFERE WITH WATER.** 

#### 5.2 Specific damage caused by substance and mixture

Serious fire hazard.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ witxture Ivalle	SEMKYD FA 50 W 60	Repreparation date	-
Form No 41	41	Revision	-
	41	Page No	5/ 12

#### **5.3 Advice for firefighters**

If there is no risk, move the container away from the fire area. Cool containers with water spray until the flames completely extinguish.

#### 6. ACCIDENTAL RELEASE MEASURES

#### **6.1 Personal protective precautions**

Avoid breathing vapor, fume or gas. Make sure that the ventilation is sufficient. Destroy everything that could cause ignition. Remove the personnel safe zone. Wear suitable protective clothing.

#### **6.2 Environmental precautions**

Be careful not to leak or spill. Avoid sewage, water spills, and spills on the soil.

#### 6.3 Methods and material for containment and cleaning up

In case of small spills, clean with sand, earth or cloth. Collect the materials used for cleaning in a separate place and dispose of them according to the hazardous waste regulations. No smoking in the place where the waste is collected, no welding, no naked fire. Ventilate the environment well.

If it spreads in large quantities, turn off all heat and sources of ignition, do not smoke. The person who cleans this area should wear a sword.

### 7. STORAGE AND HANDLING

#### 7.1 Precautions for safe handling

#### 7.1.1

Measures to prevent or control both fire and aerosol and dust formation to ensure safe handling of the substance or mixture.

Prevention of the handling of substances or mixtures which are incompatible with each other.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ whitture ivalle	SEMKYD FA 50 W 60	Repreparation date	-
Form No	41	Revision	-
		Page No	6/ 12

Reduce the spread of the substance or mixture to the environment, such as avoiding spillage or keeping it away from waterways.

7.1.2

No eating, drinking and smoking in work areas.

Washing hands after use.

Removal of contaminated clothing and protective equipment before entering food areas.

7.2 Conditions for safe stage, including any incompatibilities

**Hazards and Precautions** Flammable liquid and vapor. The mouth of the resin containers must be sealed very tightly. Even the smallest amount of material remaining in empty containers can be dangerous. Be sure not to weld the containers, be careful of static electricity, before making sure that they are emptied. The containers must be filled with water and should not be repaired without ensuring that all resin vapors have been thrown out.

**Transport:** The resin is transported while the mouths of the containers are tightly closed. Keep away from all sources of heat and flame. All vehicles must be grounded.

Storage : Storage area away from fire, sparks and it must be a cool place with air flow.

7.3	Specific	end use	

No data.

#### 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

**8.1 Control Parameters** 

#### **Exposure Limits/ standards**

The places where this material is used and stored should have adequate ventilation.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ witxture Maine	SEMKYD FA 50 W 60	Repreparation date	-
Form No 41	41	Revision	-
	1	Page No	7/ 12

#### 8.2 Exposure Controls

**8.2.1 Engineering Precautions:** Carry it according to industrial hygiene and safety regulations. Wash your hands at the end of the day.

### 8.2.2 Personal Protective Equipment



**Inhalation Protection:** Use respiratory equipment and devices that have been tested and approved in accordance with the standard.

**Eye/Face Protection:** Use protective glasses or face shields against chemical spatter that tightly enclose the face.

**Skin Protection:** Use suitable gloves. Gloves should be checked before use. Contaminated gloves should be disposed of in accordance with good laboratory practices and compliance rules. Away from synthetic clothing that can produce static electricity. This information is advisory. It should not be accepted as an approval for any particular use case.

**Hands Protection:** If skin contact is indicated, use a chemically resistant, waterproof glove complying with an approved standard.

Thermal Damage: All protective equipment suitable for use at high temperatures should be used.

### 8.3 Environmental Exposure Control

Ventilation emissions and work process equipment must be checked for compliance with environmental protection legislation requirements.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ whitture ivalle	SEMKYD FA 50 W 60	Repreparation date	-
Form No	41	Revision	-
		Page No	8/12

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties

Form	Consistent Liquid
Odour	The smell of the solvent
Colour Gardner	MAX 7
Boiling Point	150 to 205 °C (WS)
Flash Point	Open cup:41 °C (WS)
Evaporation Rate	No data.
Flammability	Flammable
Upper / lower flammability or explosive limits:	7,2% - 0.6 % (WS)
Vapor Pressure (25°C)	0,23 kPa (WS)
Vapor Density	No data
Solubility in water	Insoluble.
Viscosity (25 °C) Pa.s	3-10
Acid Number	MAX 10
Solid	%60 ± 2
Density (g/cm <sup>3</sup> )	0,95±0,02

## 9.2 Other Information

No data.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ witxture Ivalle	SEMKYD FA 50 W 60	Repreparation date	-
Form No	41	Revision	-
I OIIII I VO	71	Page No	9/ 12

<b>10. ST</b> A	ABILITY AND REAVTIVITY
10.1	The Reaction
It is	stable under normal conditions.
10.2	Chemical Stability
No o	langerous polymerization occurs
10.3	Harmful Response Potential
No o	lata.
10.4	Conditions to Avoid
Hea	t, flame, sustainable sources.
10.5	Substances to Avoid
Non	e
10.6	Hazardous Decomposition Products
No l	known hazardous decomposition products.
<b>11. TO</b>	XICOLOGICAL INFORMATION
11.1	Information of toxic effect

# 11.1

## **Acute Toxicity**

Product/ ingredient	Test	Dose
	LD50, Oral	>15000 mg/kg (rat)
White Spirit	LC50, Inhalation Vapour	>13,1 mg/l (rat vapors,4h)
White Spirit	LD50, Dermal	>3400 mg/ kg ( rabbit)

Product/ ingredient Test		Species	Score
White Spirit	Skin- Oedema	Rabbit	1
	Skin- Erythema/ Eschar	Rabbit	1,22
	Eyes- Redness of the conjunctivae	Rabbit	0,3
	Eyes- Oedema of the conjunctivae	Rabbit	0
	Eyes- Iris lesion	Rabbit	0



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ witxture realite	SEMKYD FA 50 W 60	Repreparation date	-
Form No	41	Revision	-
TOTILINO	71	Page No	10/ 12
Skin Irritation or Corrosion:Based on available data, the classification criteria are not met.Eye Irritation:Based on available data, the classification criteria are not met.			
Skin Sensitization: Not classified as a sensitizer			
Mutagenicity: Not mutagenic in a standard battery of genetic toxicological			c toxicological tests.
Carcinogenicity: Not available.			

## **<u>Reproductive Toxicity</u>:**

Product/ ingredient	Material Toxicity	Fertility	Development Toxin	Species	Dose	Exposure
White Spirit	Negative	Negative	Negative	Rat	Inhalation	-

## Specific Target Organ Toxicity ( Repeated Exposure):

Product/ ingredient	Category	Route of Exposure	Target Organs
White Spirit	Category 1	Inhalation	Central nervous system (CNS)

## **Chronic/ Other Effects:**

Not available.

<b>12. EC</b>	OLOGICAL INFORMATION
12.1	Toxicity
It doe	es not accumulate in water organisms.
12.2	Persistence and Degradability
No	data.
12.3	Bioaccumulation and Potential
No da	ata.
12.4	Mobility in Soil



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ witxture ivaille	SEMKYD FA 50 W 60	Repreparation date	-
Form No	41	Revision	-
I of in 140	71	Page No	11/ 12

Stop it from getting in the ground.

-	
12.5	Results of PBT and vPvB Assessment
No data	а.
12.6	Other Information
No data	а.
<b>13. DISE</b>	POSAL CONSIDERATIONS
12.1	Weste Due cogging Matheda
13.1	Waste Processing Methods

It is disposed in accordance with the environmental regulations. Resin-carrying containers are cleaned and reused in accordance with regulations. Disposal of containers with resin is carried out at licensed disposal facilities.

<b>14. TR</b> A	ANSPORT INFORMATION
14.1	UN No: 1263
14.2	Proper UN Transport Name: UN 1263 PAINT RELATED MATERIAL
14.3	Hazard Class: 3
14.4	Packing Group: III
14.5	Environmental Hazard: Aquatic Chronic Cat. 2
14.6	Special Precautions for the User: No data.
15. RE(	GULATORY INFORMATION
15.1	Special safety, health and environmental legislation for substance or mixture
D 1 . 4	on on the Classification Labeling and Dashing of Substance and Mintures ID C

Regulation on the Classification, Labeling and Packing of Substance and Mixtures [R.G. 11/12/2013 - 28848]

Regulation on Safety Data Sheets for Hazardous Substances and Mixtures [13/12/2014 - Official Gazette No. 29204]

Regulation on the Transport of Dangerous Goods by Road [R.G. 24/10/2013 - 28801]



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-6001	Preparation date	24.06.2020
Substance/ whitture Maine	SEMKYD FA 50 W 60	Repreparation date	-
Form No	41	Revision	-
T OF IN TWO	71	Page No	12/ 12

## **16. OTHER INFORMATION**

Update: The new format is applied.

Abbreviations:

UZEM: National Poison Advisory Center

STOT : Specific Target Organ Systemic Toxicity

Asp. Tox. 1: Aspiration Toxicity 1

Key Information Sources: This GBF SEA regulation is based on the information in Appendix 6.

Hazard Statements: H304: May be fatal if swallowed and enters airways.

Prepared by

Name Surname: PENBEGÜL İNCE

Contact: penbegul.ince@semkim.com.tr

Certification No: TÜV/01.154.08

Certification Effective Date: 09/05/2021