

Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Mixture Name	SEMKYD FA 67 D 85	Repreparation date	11.06.2020
Form No	52	Revision	2
FOIIII NO	32	Page No	1/ 11

1. SUBSTANCE/ MIXTURE AND COMPANY/ EMPLOYER IDENTIFICATION

1.1 Substance/ Mixture Identification:

Product Name: SEMKYD FA 67 D 85/ SMK-7085

1.2 Use of Material / Composition and If not recommended Use:

Component of coating or paint

1.3 Company Identification

Producer Company

Name: SEMKİM Paint and Chemicals Industry and Trade Ltd. Co.

Address: Kemalpaşa OSB Mah. 508 Sokak No 320 Kemalpaşa/İZMİR

Phone Number: 0232 878 97 80

Fax: 0232 878 97 83

E-posta: info@semkim.com

1.4 In case of emergency: 114 (UZEM)

2. HAZARDS IDENTIFICATION

2.1 Classification of Substance/Mixture

Physical Effect	No Application	
Health Effect	Aspiration Tox. 1	H304
Health Effect	Aspiration Tox. 1	EUH066
Environmental Effect	No Application	



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Mixture Name	SEMKYD FA 67 D 85	Repreparation date	11.06.2020
Form No	52	Revision	2
1 01111 140	FOIII NO 32	Page No	2/ 11

2.2 Label Elements



GHS Symbol:

Signal Word: Danger

Hazard Statements

EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways.

Precautionary Statements

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor /

physician.

P405: Keep it under lock.

P501: Please dispose of contents/container.

3. INFORMATION ON COMPOSITION CONTENT

Substance Name	CAS No	EC No	Reach No	Content %	Hazard Code and Category Code	Hazard Statement Code
D 60	64742-48-9	918-481-9	01- 21194572 73-39- 0009	15	Aspiration Tox. 1	H304 EUH066
Alkyd Resin				85		



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Whiture Name	SEMKYD FA 67 D 85	Repreparation date	11.06.2020
Form No	52	Revision	2
Form No	32	Page No	3/ 11

4. FIRST AID MEASURES

4.1 Description of first-aid measures

Inhalation: Get medical help immediately. Move away from the environment and immediately into fresh air. If not breathing, do artificial respiration. If breathing difficulties give oxygen.

Skin Contact: Get medical help immediately. Remove contaminated clothing and shoes and immediately wash your skin with plenty of water for at least 15 minutes.

Eye Contact: Wash immediately with large quantities of water for 15 minutes. If irritation persist call a doctor.

Ingestion: Do not induce vomiting. Chemical vapors may escape during lungs. Immediately give 1-2 cups of water or milk to the person. If consciousness is off, never give anything. Get medical help urgently.

4.2 Most important symptoms and effects, both acute and delayed

The known symptoms and effects are indicated on the label. (See Section 2.2)

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Support psychologically and behave according to findings.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

To put out the fire foam, dry chemical powder and use the CO₂ extinguishing devices. **DO NOT STRICTLY INTERFERE WITH WATER.**

5.2 Specific damage caused by substance and mixture

Serious fire hazard.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Mixture Name	SEMKYD FA 67 D 85		11.06.2020
Form No	52	Revision	2
Form No	52	Page No	4/ 11

5.3 Advice for firefighters

If there is no risk, move the container away from the fire area. Cool containers with water spray until the flames completely extinguish.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal protective precautions

Avoid breathing vapor, fume or gas. Make sure that the ventilation is sufficient. Destroy everything that could cause ignition. Remove the personnel safe zone. Wear suitable protective clothing.

6.2 Environmental precautions

Be careful not to leak or spill. Avoid sewage, water spills, and spills on the soil.

6.3 Methods and material for containment and cleaning up

In case of small spills, clean with sand, earth or cloth. Collect the materials used for cleaning in a separate place and dispose of them according to the hazardous waste regulations. No smoking in the place where the waste is collected, no welding, no naked fire. Ventilate the environment well.

If it spreads in large quantities, turn off all heat and sources of ignition, do not smoke. The person who cleans this area should wear a sword.

7. STORAGE AND HANDLING

7.1 Precautions for safe handling

7.1.1

Measures to prevent or control both fire and aerosol and dust formation to ensure safe handling of the substance or mixture.

Prevention of the handling of substances or mixtures which are incompatible with each other.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Whiture Name	SEMKYD FA 67 D 85		11.06.2020
Form No	52	Revision	2
Form No	32	Page No	5/ 11

Reduce the spread of the substance or mixture to the environment, such as avoiding spillage or keeping it away from waterways.

7.1.2

No eating, drinking and smoking in work areas.

Washing hands after use.

Removal of contaminated clothing and protective equipment before entering food areas.

7.2 Conditions for safe stage, including any incompatibilities

Hazards and Precautions Flammable liquid and vapor. The mouth of the resin containers must be sealed very tightly. Even the smallest amount of material remaining in empty containers can be dangerous. Be sure not to weld the containers, be careful of static electricity, before making sure that they are emptied. The containers must be filled with water and should not be repaired without ensuring that all resin vapors have been thrown out.

Transport: The resin is transported while the mouths of the containers are tightly closed. Keep away from all sources of heat and flame. All vehicles must be grounded.

Storage: Storage area away from fire, sparks and it must be a cool place with air flow.

7.3 Specific end use

No data.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control Parameters

Exposure Limits/ standards

The places where this material is used and stored should have adequate ventilation.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Mixture Name	SEMKYD FA 67 D 85	Repreparation date	11.06.2020
Form No	52	Revision	
1 01111 140	52	Page No	6/ 11

8.2 Exposure Controls

8.2.1 Engineering Precautions: Carry it according to industrial hygiene and safety regulations. Wash your hands at the end of the day.

8.2.2 Personal Protective Equipment











Inhalation Protection: Use respiratory equipment and devices that have been tested and approved in accordance with the standard.

Eye/Face Protection: Use protective glasses or face shields against chemical spatter that tightly enclose the face.

Skin Protection: Use suitable gloves. Gloves should be checked before use. Contaminated gloves should be disposed of in accordance with good laboratory practices and compliance rules. Away from synthetic clothing that can produce static electricity. This information is advisory. It should not be accepted as an approval for any particular use case.

Hands Protection: If skin contact is indicated, use a chemically resistant, waterproof glove complying with an approved standard.

Thermal Damage: All protective equipment suitable for use at high temperatures should be used.

8.3 Environmental Exposure Control

Ventilation emissions and work process equipment must be checked for compliance with environmental protection legislation requirements.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Witxture Ivaille	SEMKYD FA 67 D 85		11.06.2020
Form No	52	Revision	2
TOINI NO	52	Page No	7/ 11

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties

Form	Consistent Liquid
Odour	The smell of the solvent
Colour Gardner	MAX 7
Boiling Point	170-225 °C (D60)
Flash Point	Closed cup ≥ 62 °C (D60)
Evaporation Rate	No data.
Flammability	Flammable
Upper / lower flammability or explosive limits:	7% - 0.6 % (D60)
Vapor Pressure (20°C)	0,04 kPa (D60)
Vapor Density	No data
Solubility in water	Insoluble.
Viscosity (25 °C) Pa.s	4-9
Acid Number	MAX 10
Solid	$\%85 \pm 2$
Density (g/cm ³)	0,99±0,02

9.2 Other Information

No data.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Whiture Name	SEMKYD FA 67 D 85	Repreparation date	11.06.2020
Form No	52	Revision	2
Form No	32	Page No	8/ 11

10. STABILITY AND REAVTIVITY

10.1 The Reaction

It is stable under normal conditions.

10.2 Chemical Stability

No dangerous polymerization occurs..

10.3 Harmful Response Potential

No data.

10.4 Conditions to Avoid

Heat, flame, sustainable sources.

10.5 Substances to Avoid

None

10.6 Hazardous Decomposition Products

No known hazardous decomposition products.

11. TOXICOLOGICAL INFORMATION

11.1 Information of toxic effect

Acute Toxicity

Product/ ingredient	Test	Dose
	LD50, Oral	>5000 mg/kg (rat)
D 60	LC50, Inhalation Vapour	>4951 mg/l (rat vapors,4h)
D 60	LD50, Dermal	>3000 mg/ kg (rabbit)

Product/ ingredient	Test	Species	Score
	Skin- Erythema/ Eschar	Rabbit	2
D 60	Eyes- Edema	Rabbit	0
	Eyes- Edema of the conjunctivae	Rabbit	0

Skin Irritation or Corrosion: Based on available data, the classification criteria are not met.

Eye Irritation: Based on available data, the classification criteria are not met.



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Mixture Name	SEMKYD FA 67 D 85	Repreparation date	11.06.2020
Form No	52	Revision	2
I OIIII IVO		Page No	9/ 11

Mutagenicity: No known significant effects or critical hazards.

Carcinogenicity: No known significant effects or critical hazards.

Reproductive Toxicity:

Product/ ingredient	Material Toxicity	Fertility	Development Toxin	Species	Dose	Exposure
D 60	Negative	Negative	-	Rat	Oral	1

Specific Target Organ Toxicity (Repeated Exposure): Not available

Chronic/ Other Effects: Not available.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

It does not accumulate in water organisms.

12.2 Persistence and Degradability

No data.

12.3 Bioaccumulation and Potential

No data.

12.4 Mobility in Soil

Stop it from getting in the ground.

12.5 Results of PBT and vPvB Assessment

No data.

12.6 Other Information

No data.

13. DISPOSAL CONSIDERATIONS

13.1 Waste Processing Methods



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Whiture Name	SEMKYD FA 67 D 85	Repreparation date	11.06.2020
Form No	52	Revision	2
		Page No	10/ 11

It is disposed in accordance with the environmental regulations. Resin-carrying containers are cleaned and reused in accordance with regulations. Disposal of containers with resin is carried out at licensed disposal facilities.

14. TRANSPORT INFORMATION

- **14.1** UN No: 1263
- **14.2 Proper UN Transport Name**: UN 1263 PAINT RELATED MATERIAL
- **14.3** Hazard Class: 3
- 14.4 Packing Group: III
- **14.5 Environmental Hazard**: There is no environmental damage.
- **14.6 Special Precautions for the User:** No data.

15. REGULATORY INFORMATION

15.1 Special safety, health and environmental legislation for substance or mixture

Regulation on the Classification, Labeling and Packing of Substance and Mixtures [R.G. 11/12/2013 - 28848]

Regulation on Safety Data Sheets for Hazardous Substances and Mixtures [13/12/2014 - Official Gazette No. 29204]

Regulation on the Transport of Dangerous Goods by Road [R.G. 24/10/2013 - 28801]

16. OTHER INFORMATION

Update: The new format is applied.

Abbreviations:

UZEM: National Poison Advisory Center



Prepared in accordance with the Regulation on Preparation of Safety Data Sheets for Hazardous Substances and Mixtures (Official Journal no. 13.12.2014 - 29204).

Substance/Mixture Name	SMK-7085	Preparation date	12.11.2019
Substance/Whiture Name	SEMKYD FA 67 D 85	Repreparation date	11.06.2020
Form No	52	Revision	2
		Page No	11/11

Asp. Tox. 1: Aspiration Toxicity 1

Key Information Sources: This GBF SEA regulation is based on the information in Appendix 6.

Prepared by

Name Surname: PENBEGÜL İNCE

Contact: penbegul.ince@semkim.com.tr

Certification No: TÜV/01.154.08

Certification Effective Date: 09/05/2021